# HYDRAULIC 4-BOLT FLANGE NPTF PORT




** Imágenes referenciales*
*** Algunas características pueden variar sin previo aviso, venta sujeta a stock disponible*

FECHA
: 11/24/2026 12:11 AM

SKU
: 9862

MARCA
: DIXON VALVE

MODELO
: C6143K3232NPT

Applications:
Flange adapters for hydraulic systems make installation of components easier, especially in applications with limited space.

Specifications:
SAE J518-1 / ISO 6162-1

Features:
Standard pressure
Flanges are constructed with an O-ring seal to eliminate leakage
Includes bolt kit with Buna O-ring

Construction:
Pad size: 2"

Available Options:
Also available in 316L stainless steel, contact Dixon

Note:
Connection type opposite 4-bolt flange connection can de-rate maximum working pressure

Safety notes:
Pressure rating given at ambient temperature 70°F
WARNING: Cancer and Reproductive Harm- www.P65Warnings.ca.gov



2645 Executive Park Drive, Weston, Fort Lauderdale, FL 33331, EEUU
sales@kmxusa.us
www.kmxusa.us

## ESPECIFICACIONES TÉCNICAS

| | |
|---|---|
| **Factory Part Number** | C6143K3232NPT |
| **Fitting Type** | O-ring |
| **Material** | Carbon Steel |
| **Maximum Operating Pressure** | 3000 PSI (21 MPa) |
| **Port** | 2" |
| **Style** | Code 61 |
| **Thread Size** | 2" - 11-1/2 |
| **Torque** | Grade 8 UNC: 111 lb-ft |
| **Weight Lb** | 3.5500 |



KMX
2645 Executive Park Drive, Weston, Fort Lauderdale, FL 33331, EEUU
sales@kmxusa.us
www.kmxusa.us