# HYDRAULIC 4-BOLT FLANGE PIPE SOCKET WELD




** Imágenes referenciales*
*** Algunas características pueden variar sin previo aviso, venta sujeta a stock disponible*

FECHA
: 11/23/2026 07:35 PM

SKU
: 9886

MARCA
: DIXON VALVE

MODELO
: C61611212PSW

Applications:
Flange adapters for hydraulic systems make installation of components easier, especially in applications with limited space.

Specifications:
SAE J518-1 / ISO 6162-1

Features:
Standard pressure
Flanges are constructed with an O-ring seal to eliminate leakage
Flat face flange must be used with O-ring flange
No bolt kit is included with flat face flange

Construction:
Pad size: 3/4"

Available Options:
Also available in 316L stainless steel, contact Dixon

Note:
Connection type opposite 4-bolt flange connection can de-rate maximum working pressure

Safety notes:
Pressure rating given at ambient temperature 70°F
WARNING: Cancer and Reproductive Harm- www.P65Warnings.ca.gov



2645 Executive Park Drive, Weston, Fort Lauderdale, FL 33331, EEUU
sales@kmxusa.us
www.kmxusa.us

## ESPECIFICACIONES TÉCNICAS

| | |
|---|---|
| **Factory Part Number** | C61611212PSW |
| **Fitting Type** | Flat Face |
| **Material** | Carbon Steel |
| **Maximum Operating Pressure** | 5000 PSI (35 MPa) |
| **Port** | 3/4" |
| **Style** | Code 61 |
| **Torque** | Grade 8 UNC: 44 lb-ft |
| **Weight Lb** | 0.7350 |



KMX

2645 Executive Park Drive, Weston, Fort Lauderdale, FL 33331, EEUU
sales@kmxusa.us

www.kmxusa.us