KING CRIMP® STYLE FERRULE CARBON STEEL



** Imágenes referenciales*
*** Algunas características pueden variar sin previo aviso, venta sujeta a stock disponible*

FECHA
: 11/23/2026 10:47 PM

SKU
: 23410

MARCA
: DIXON VALVE

MODELO
: CF125-3CS

Use:
For use with crimp style shanks.

Safety notes:
Only use the crimp style shanks with the crimp style sleeves and ferrules. Due to differences in dimensions and tolerances for safety reasons, do not interchange other manufacturer's products with Dixon products.
Pressure rating given at 70°F, consult Dixon for pressure rating at elevated temperatures.
WARNING: Cancer and Reproductive Harm- www.P65Warnings.ca.gov

ESPECIFICACIONES TÉCNICAS

Factory Part Number	CF125-3CS
Hose ID	1-1/4"
Hose OD From	1-41/64" (41.67mm)
Hose OD To	1-44/64" (42.86mm)
ID	1.75" (44.45mm)
Length	2-13/16"
Material	Carbon Steel
Wall Thickness	0.06
Weight Lb	0.2630
Working Pressure	250 PSIG with King Crimp Cam & Groove, 350 PSIG with King Crimp ST Nipple

2645 Executive Park Drive, Weston, Fort Lauderdale, FL 33331, EEUU
sales@kmxusa.us
www.kmxusa.us