KING CRIMP® STYLE FERRULE 304 STAINLESS STEEL



** Imágenes referenciales*
*** Algunas características pueden variar sin previo aviso, venta sujeta a stock disponible*

FECHA
: 11/24/2026 12:05 AM

SKU
: 23483

MARCA
: DIXON VALVE

MODELO
: CF300-2SS

Use:
For use with crimp style shanks.

Safety notes:
Only use the crimp style shanks with the crimp style sleeves and ferrules. Due to differences in dimensions and tolerances for safety reasons, do not interchange other manufacturer's products with Dixon products.
Pressure rating given at 70°F, consult Dixon for pressure rating at elevated temperatures.
WARNING: Cancer and Reproductive Harm- www.P65Warnings.ca.gov

ESPECIFICACIONES TÉCNICAS

Factory Part Number	CF300-2SS
Hose ID	3"
Hose OD From	3-17/64" (82.95mm)
Hose OD To	3-20/64" (84.14mm)
ID	3.375" (85.73mm)
Length	4"
Material	304 Stainless Steel
Wall Thickness	0.09
Weight Lb	1.0950
Working Pressure	150 PSIG with King Crimp Cam & Groove, 300 PSIG with King Crimp ST Nipple

2645 Executive Park Drive, Weston, Fort Lauderdale, FL 33331, EEUU
sales@kmxusa.us
www.kmxusa.us