# CJ-SERIES PNEUMATIC FEMALE THREADED PLUG





** Imágenes referenciales*
*** Algunas características pueden variar sin previo aviso, venta sujeta a stock disponible*

FECHA
: 11/23/2026 08:04 PM

SKU
: 10114

MARCA
: DIXON VALVE

MODELO
: CJ3BF3-B

Specifications:
Rated pressure for connected Brass Coupler & Brass Plug: 300 PSI (20 bar) Maximum Working and 4,400 PSI (300 bar) Burst

Construction:
Machined components are manufactured using solid brass bar stock.

Compatibility & Interchange Data:
European High-Flow Interchange
Interchanges with Rectus 27KA, CEJN 410 and other like designs

Safety notes:
It is important to be safe when installing quick disconnect couplings into a pneumatic circuit. Never install a pneumatic coupling directly into an air tool, use a piece of hose that is at least 18" long, between the tool and the coupling, to prevent damage to the coupling. To protect the operator, safety devices, such as a safety check valve and safety cable should be installed in case there is a hose or coupling failure.
WARNING: Cancer and Reproductive Harm- www.P65Warnings.ca.gov

## ESPECIFICACIONES TÉCNICAS

| | |
|---|---|
| **Body Size** | 3/8" |
| **Factory Part Number** | CJ3BF3-B |
| **Hex** | 7/8" |
| **Length** | 1.50" (38.0mm) |
| **Material** | Brass |
| **Maximum OD** | 1.01" (25.7mm) |



2645 Executive Park Drive, Weston, Fort Lauderdale, FL 33331, EEUU
sales@kmxusa.us
www.kmxusa.us

## ESPECIFICACIONES TÉCNICAS

| | |
|---|---|
| **Pressure Rating** | See Product Details |
| **Temperature Range** | -40°F to +250°F (-40°C to +121°C) |
| **Thread** | BSPP |
| **Thread Size** | 3/8" |
| **Weight Lb** | 0.1000 |



KMX

2645 Executive Park Drive, Weston, Fort Lauderdale, FL 33331, EEUU

sales@kmxusa.us

www.kmxusa.us