
CJ-SERIES PNEUMATIC FEMALE THREADED PLUG





** Imágenes referenciales*
*** Algunas características pueden variar sin previo aviso, venta sujeta a stock disponible*

FECHA
: 11/23/2026 06:11 PM

SKU
: 10121

MARCA
: DIXON VALVE

MODELO
: CJ3F3

Specifications:
Rated pressure for connected Brass Coupler & Steel Plug: 300 PSI (20 bar) Maximum Working and 8,000 PSI (552 bar) Burst

Construction:
Machined components are manufactured using solid steel bar stock.
Steel componentry is plated using ROHS Compliant Trivalent Chrome.

Compatibility & Interchange Data:
European High-Flow Interchange
Interchanges with Rectus 27KA, CEJN 410 and other like designs

Safety notes:
It is important to be safe when installing quick disconnect couplings into a pneumatic circuit. Never install a pneumatic coupling directly into an air tool, use a piece of hose that is at least 18" long, between the tool and the coupling, to prevent damage to the coupling. To protect the operator, safety devices, such as a safety check valve and safety cable should be installed in case there is a hose or coupling failure.
WARNING: Cancer and Reproductive Harm- www.P65Warnings.ca.gov

2645 Executive Park Drive, Weston, Fort Lauderdale, FL 33331, EEUU
sales@kmxusa.us
www.kmxusa.us

ESPECIFICACIONES TÉCNICAS

Body Size	3/8"
Factory Part Number	CJ3F3
Hex	7/8"
Length	1.50" (38.0mm)
Material	Steel
Maximum OD	1.01" (25.7mm)
Pressure Rating	See Product Details
Temperature Range	-40°F to +250°F (-40°C to +121°C)
Thread	NPT
Thread Size	3/8"
Weight Lb	0.1500

KMX

2645 Executive Park Drive, Weston, Fort Lauderdale, FL 33331, EEUU
sales@kmxusa.us

www.kmxusa.us