CLEAR PVC TUBING



** Imágenes referenciales*
*** Algunas características pueden variar sin previo aviso, venta sujeta a stock disponible*

FECHA
: 11/23/2026 09:36 PM

SKU
: 10137

MARCA
: DIXON VALVE

MODELO
: CL1216

Applications:
For non-critical hospital use such as suction and draining
For low pressure liquid and pneumatic applications

Use:
Designed to be used with standard shank fittings

Specifications:
Finished product meets USP Class VI
NSF-51 Certified
Reach and RoHS compliant
Raw materials meet California Proposition 65

Construction:
Made from non-toxic ingredients conforming to FDA standards
Phthalate, DEHP, and BPA free

Note:
Shipped in individually boxed bundles

Safety notes:
WARNING: Cancer and Reproductive Harm- www.P65Warnings.ca.gov

2645 Executive Park Drive, Weston, Fort Lauderdale, FL 33331, EEUU
sales@kmxusa.us
www.kmxusa.us

ESPECIFICACIONES TÉCNICAS

Color	Clear
Factory Part Number	CL1216
Material	PVC
Maximum Temperature	175°F (79.4°C)
Tube ID	3/4"
Tube OD	1"
Weight Lb	21.3600
Working Pressure	61 PSI @70°F

KMX
2645 Executive Park Drive, Weston, Fort Lauderdale, FL 33331, EEUU
sales@kmxusa.us
www.kmxusa.us