DQC CM-SERIES INDUSTRIAL MOLD INTERCHANGE PLUG MALE NPTF





FECHA
: 11/23/2026 11:44 PM

SKU
: 10176

MARCA
: DIXON VALVE

MODELO
: CM4M4-B

Specifications:
Rated pressure for connected Brass Unvalved Coupler and Brass Plug: 300 PSI (20 bar) Maximum Working and 4,900 PSI (340 bar) Burst

Construction:
Machined components are manufactured using solid bar stock

Compatibility & Interchange Data:
Mold Coolant Interchange
Foster Series- FJT, Hansen Flo-Temp, Tomco MC-Series, Parker Moldmate, DME Jiffy-Tite

Safety notes:
Maximum working and burst pressure is based on a coupled set, contact Dixon for pressure ratings.
WARNING: Cancer and Reproductive Harm- www.P65Warnings.ca.gov

** Imágenes referenciales*
*** Algunas características pueden variar sin previo aviso, venta sujeta a stock disponible*

ESPECIFICACIONES TÉCNICAS

Body Size	1/2"
Factory Part Number	CM4M4-B
Hex	7/8"
Length	1.69"
Material	Brass
Maximum OD	1.01"
Temperature Range	-90°F to +400°F (-68°C to +205°C)
Thread	Male NPTF

2645 Executive Park Drive, Weston, Fort Lauderdale, FL 33331, EEUU
sales@kmxusa.us
www.kmxusa.us

ESPECIFICACIONES TÉCNICAS

Thread Size	1/2"-14
Weight Lb	0.1000

KMX
2645 Executive Park Drive, Weston, Fort Lauderdale, FL 33331, EEUU
sales@kmxusa.us
www.kmxusa.us