# KING CRIMP® STYLE SLEEVE ALUMINUM




** Imágenes referenciales*
*** Algunas características pueden variar sin previo aviso, venta sujeta a stock disponible*

FECHA
: 11/23/2026 10:01 PM

SKU
: 23617

MARCA
: DIXON VALVE

MODELO
: CS150-3AL

Use:
For use with crimp style shanks.
For liquid service only.

Safety notes:
Only use the crimp style shanks with the crimp style sleeves and ferrules. Due to differences in dimensions and tolerances for safety reasons, do not interchange other manufacturer's products with Dixon products.
Pressure rating given at 70°F, consult Dixon for pressure rating at elevated temperatures.
WARNING: Cancer and Reproductive Harm- www.P65Warnings.ca.gov

## ESPECIFICACIONES TÉCNICAS

| | |
|---|---|
| **Factory Part Number** | CS150-3AL |
| **Hose ID** | 1-1/2" |
| **Hose OD From** | 1-49/64" |
| **Hose OD To** | 1-52/64" |
| **ID** | 1.875" |
| **Length** | 2-1/2" |
| **Material** | Aluminum |
| **Wall Thickness** | 0.062 |
| **Weight Lb** | 0.2560 |
| **Working Pressure** | 250 PSIG with King Crimp Cam & Groove,<br/>300 PSIG with King Crimp ST Nipple |



2645 Executive Park Drive, Weston, Fort Lauderdale, FL 33331, EEUU
sales@kmxusa.us
www.kmxusa.us