DQC CVV-SERIES EUROPEAN INTERCHANGE FEMALE PLUG





FECHA
: 11/24/2026 01:42 AM

SKU
: 10358

MARCA
: DIXON VALVE

MODELO
: CVV10F10

Construction:
Machined components are manufactured using solid bar stock
Steel retaining rings and springs maximize service life in rugged environments.
Steel componentry is plated using ROHS Compliant Trivalent Chrome.
Nipples have a PTFE Anti-Extrusion ring to prevent O-Ring damage during dynamic impulse service.

Compatibility & Interchange Data:
European Screw-Together Interchange
Inteva STG-Series, Faster CVV-Series, DNP PVV3, Voswinkel Type-HS, Stucchi VD Series

Safety notes:
WARNING: Cancer and Reproductive Harm- www.P65Warnings.ca.gov

** Imágenes referenciales*
*** Algunas características pueden variar sin previo aviso, venta sujeta a stock disponible*

ESPECIFICACIONES TÉCNICAS

Body Size	1-1/4"
Burst Pressure	17600 PSI (1200 Bar)
Factory Part Number	CVV10F10
Hex	50mm
Length	5.91" (150.0mm)
Material	Steel
Maximum OD	2.76" (70.0mm)
Maximum Operating Pressure	4400 PSI (300 Bar)
Temperature Range	-40°F to +250°F (-40°C to +121°C)

2645 Executive Park Drive, Weston, Fort Lauderdale, FL 33331, EEUU
sales@kmxusa.us
www.kmxusa.us

ESPECIFICACIONES TÉCNICAS

Thread	Female NPTF
Thread Size	1-1/4" - 11-1/2
Weight Lb	4.3200

KMX
2645 Executive Park Drive, Weston, Fort Lauderdale, FL 33331, EEUU
sales@kmxusa.us
www.kmxusa.us