WILKERSON FRL'S D18 COMBINATION UNIT



** Imágenes referenciales*
*** Algunas características pueden variar sin previo aviso, venta sujeta a stock disponible*

FECHA
: 11/23/2026 06:49 PM

SKU
: 26196

MARCA
: DIXON VALVE

MODELO
: D18-04M

Features:
Light weight, Ready-to-Mount assembly comes standard with pressure gauge and modular T-Bracket/Joiner Assembly
Components integrated into single unit
Modern design and appearance
Quick disconnect bowl / bowl guard
5 micron element
4.09 oz. bowl/lubricator
Regulator is self-relieving, with a 0-125 PSI adjusting range and is supplied with a gauge
1.72 oz. bowl/filter

Safety notes:
FRL\'s are designed for air service only, unless otherwise indicated.
SCFM ratings at 150 PSIG inlet pressure
WARNING: Cancer and Reproductive Harm- www.P65Warnings.ca.gov

ESPECIFICACIONES TÉCNICAS

Description	Manual Drain, Transparent Bowl and Guard
Factory Part Number	D18-04M
Flow	90 SCFM
Maximum Operating Pressure	150 PSIG (10.3 Bar)
Size	1/2"
Temperature Range	32°F to 125°F (0°C to 52°C)
Weight Lb	2.9800

2645 Executive Park Drive, Weston, Fort Lauderdale, FL 33331, EEUU
sales@kmxusa.us
www.kmxusa.us