NON-SAFETY RUBBER TIP BLOW GUN



** Imágenes referenciales*
*** Algunas características pueden variar sin previo aviso, venta sujeta a stock disponible*

FECHA
: 11/23/2026 08:48 PM

SKU
: 11128

MARCA
: DIXON VALVE

MODELO
: D201

Use:
They may be used for cleaning purposes only if the air supply (inlet pressure) has been reduced to 30 PSI or less.
The conical, rubber tip can also be used to create a seal between the blow gun and fluid lines (or any other opening).

Features:
The rubber tip will not scratch or mar delicate surfaces.
Blow gun body is designed to comfortably fit the contour of the hand, minimizing user fatigue.
Large lever with vinyl grip further adds to the ergonomic design and allows for easy air flow activation.

Construction:
Chrome plated zinc die cast body, nickel plated steel lever, vinyl thumb grip, stainless steel spring, brass valve, Buna-N seals and rubber tip with a nickel plated brass base provide superior corrosion resistance.
Base of the tip is nickel-plated brass for additional corrosion resistance.

Safety notes:
Safety glasses or shield must be worn when using any blow gun.
Must be used on air lines having a maximum regulated pressure of 30 PSI in order to comply with OSHA Standard 1910.242 (B).
Non-Safety blow guns do not have a safety by-pass to prevent buildup of tip pressure in the event of tip blockage. They may be used for cleaning purposes only if the air supply (inlet pressure) has been reduced to 30 PSI or less.
WARNING: Cancer and Reproductive Harm- www.P65Warnings.ca.gov

2645 Executive Park Drive, Weston, Fort Lauderdale, FL 33331, EEUU
sales@kmxusa.us
www.kmxusa.us

ESPECIFICACIONES TÉCNICAS

Factory Part Number	D201
Inlet	1/4" female NPT
Weight Lb	0.4300

KMX
2645 Executive Park Drive, Weston, Fort Lauderdale, FL 33331, EEUU
sales@kmxusa.us
www.kmxusa.us