PREMIUM SAFETY BLOW GUN

FECHA
: 11/23/2026 10:53 PM

SKU
: 11132

MARCA
: DIXON VALVE

MODELO
: D204-30P



** Imágenes referenciales*
*** Algunas características pueden variar sin previo aviso, venta sujeta a stock disponible*

Specifications:
The premium safety blow gun is designed to conform to OSHA Standard 1910.242 (B) permitting a maximum of 30 PSI outlet pressure when dead ended based on a maximum of 150 PSI inlet pressure as well as OSHA Standard 1910.95 regulating occupational noise level exposure.

Features:
Blow gun body is designed to comfortably fit the contour of the hand, minimizing user fatigue.
Large lever with black vinyl grip further adds to the ergonomic design and allows for easy air flow activation.

Construction:
Zinc die cast body with a black powder coat finish, nickel plated steel lever, vinyl thumb grip, stainless steel spring, brass valve, Buna-N seals and nickel plated brass tip.

Safety notes:
Safety glasses or shield must be worn when using any blow gun.
WARNING: Cancer and Reproductive Harm- www.P65Warnings.ca.gov

2645 Executive Park Drive, Weston, Fort Lauderdale, FL 33331, EEUU
sales@kmxusa.us
www.kmxusa.us

ESPECIFICACIONES TÉCNICAS

Factory Part Number	D204-30P
Inlet	1/4" female NPT
Weight Lb	0.4425

KMX
2645 Executive Park Drive, Weston, Fort Lauderdale, FL 33331, EEUU
sales@kmxusa.us
www.kmxusa.us