
BAYLOC® DRY DISCONNECT ADAPTER X 150# ASA FLANGE



** Imágenes referenciales*
*** Algunas características pueden variar sin previo aviso, venta sujeta a stock disponible*

FECHA
: 11/24/2026 01:42 AM

SKU
: 27417

MARCA
: DIXON VALVE

MODELO
: DBAF78-200

Applications:
Dry disconnects help prevent spillage from normal or accidental disconnects. A spring loaded sealing device is designed to "snap" closed should the valve become disconnected with the poppet open, significantly limiting liquid loss.
Use:
Use with DBC or D2C style couplers
Use with standard cam and groove dust caps sized one size larger than the dry disconnect size
Use Cam & Groove Dust Cap Size: 2-1/2"
Construction:
Stainless steel piston
Stainless steel corrosion resistance is comparable to 304 stainless steel
Compatibility & Interchange Data:
Compatible with most other brands of cam and groove style dry disconnects
Fully interchangeable with Kamvalok (OPW trademark) style fittings
Note:
Contact Dixon™ at 800-355-1991 for chemical compatibility, size, material selection and special configurations.
Safety notes:
For pressure ratings at other temperatures, contact Dixon™.

WARNING: Cancer and Reproductive Harm- www.P65Warnings.ca.gov

2645 Executive Park Drive, Weston, Fort Lauderdale, FL 33331, EEUU
sales@kmxusa.us
www.kmxusa.us

ESPECIFICACIONES TÉCNICAS

Adapter Size	2-1/2"
Description	Cam & Groove Style
Flange Size	2"
Material	Stainless Steel
Maximum Operating Pressure	150 PSI at 70°F(21°C)
Factory Part Number	DBAF78-200
Seal	FKM-GFLT

KMX

2645 Executive Park Drive, Weston, Fort Lauderdale, FL 33331, EEUU
sales@kmxusa.us

www.kmxusa.us