BAYLOC? DRY DISCONNECT COUPLER X FEMALE NPT





** Imágenes referenciales*
*** Algunas características pueden variar sin previo aviso, venta sujeta a stock disponible*

FECHA
: 11/24/2026 01:13 AM

SKU
: 11347

MARCA
: DIXON VALVE

MODELO
: DBC63-150

Applications:
Dry disconnects help prevent spillage from normal or accidental disconnects. A spring loaded sealing device is designed to "snap" closed should the valve become disconnected with the poppet open, significantly limiting liquid loss.

Use:
Use with DBA style adapters
Use with standard cam and groove dust plug sized one size larger than the dry disconnect size
Use Cam & Groove Dust Plug Size: 2"

Specifications:
Canadian registration number CRN # OH14044 all provinces

Features:
Coupler has automatic closing poppet assembly
Heavy duty construction provides long service life
Stainless steel handle allows product exposure to corrosive chemicals or washdown service
Strong handle attachment prevents bending of crank assembly
Dixon EZ Boss-Lock cam arms provide added security from accidental opening due to vibration or snagging. Very easy to use, just close the arms and they lock, to open simply lift the lever.
Optional coupler lock for handle to prevent unintentional opening

Construction:
Stainless steel internals
Heavy duty stainless steel handle, crank and link

Compatibility & Interchange Data:
Compatible with most other brands of cam and groove style dry disconnects

2645 Executive Park Drive, Weston, Fort Lauderdale, FL 33331, EEUU
sales@kmxusa.us
www.kmxusa.us

Fully interchangeable with Kamvalok (OPW trademark) style fittings

Note:

Contact Dixon™ at 800-355-1991 for chemical compatibility, size, material selection and special configurations.

Safety notes:

Must be used with a DBA (Dry Break Cam & Groove) Style adapter for coupler to operate. Adapter sold separately.

For pressure ratings at other temperatures, contact Dixon™.

WARNING: Cancer and Reproductive Harm- www.P65Warnings.ca.gov

ESPECIFICACIONES TÉCNICAS

Coupler Size	2"
Description	Cam & Groove Style
Factory Part Number	DBC63-150
Female Thread	NPT
Female Thread Size	1-1/2"
Material	Aluminum
Maximum Operating Pressure	210 PSI at 70°F(21°C)
Seal	PTFE Encapsulated Silicone
Weight Lb	4.2000

KMX

2645 Executive Park Drive, Weston, Fort Lauderdale, FL 33331, EEUU

sales@kmxusa.us

www.kmxusa.us