PARKER E-Z-MATE INDUSTRIAL COUPLER MALE NPT



** Imágenes referenciales*
*** Algunas características pueden variar sin previo aviso, venta sujeta a stock disponible*

FECHA
: 11/23/2026 11:53 PM

SKU
: 11466

MARCA
: DIXON VALVE

MODELO
: DC9SE

Specifications:
ISO 4414 requirements for a controlled pressure release system

Features:
Ez-Mate couplings combine push-to-connect, exhaust-style action with a self-locking valve sleeve to guard against accidental disconnection.

How it works:
Simply follow the on-off arrow stamped on the yellow chromate valve sleeve. Valve sleeve acts as an integral shut-off valve that allows connection and disconnection at zero pressure. When the sleeve is moved to shut off air flow, it automatically vents downstream allowing for disconnection at zero pressure and eliminating the risk of hose whip.

Safety notes:
Not recommended for vacuum service
WARNING: Cancer and Reproductive Harm- www.P65Warnings.ca.gov

ESPECIFICACIONES TÉCNICAS

Body Size	1/2"
Factory Part Number	DC9SE
Flow	150 CFM at 100 PSI
Male Thread	NPT
Male Thread Size	1/2"-14
Material	Steel
Pressure Rating	300 PSI
Temperature Range	-40°F to +250°F (-40°C to +121°C)

2645 Executive Park Drive, Weston, Fort Lauderdale, FL 33331, EEUU
sales@kmxusa.us
www.kmxusa.us

ESPECIFICACIONES TÉCNICAS

Weight Lb	0.7300

KMX
2645 Executive Park Drive, Weston, Fort Lauderdale, FL 33331, EEUU
sales@kmxusa.us
www.kmxusa.us