DIXON MANNTEK DRY DISCONNECT STEAM COUPLER X FEMALE NPT



** Imágenes referenciales*
*** Algunas características pueden variar sin previo aviso, venta sujeta a stock disponible*

FECHA
: 11/24/2026 01:59 AM

SKU
: 23881

MARCA
: DIXON VALVE

MODELO
: DDSC100SS

Applications:
Designed to fit hoses carrying steam used in chemical (heating), pharmaceutical (disinfection and sterilization) and at loading bays.

Features:
Unintentional separation is eliminated preventing accidents and avoiding unintended down time
Performance unaffected by surface rust

Construction:
Coupling housing and all inner parts: stainless steel
Seals: EPDM 291
Couplers supplied with double handles

Available Options:
Lockable versions are available on 1-1/2" and 2", contact Dixon
Other seal materials are available, contact Dixon

Safety notes:
Note. Pressurized steam is an extremely dangerous commodity. Only hose, fittings, clamps and accessory items that have been approved for steam service should ever be used! Never use an unapproved item for steam service. Always follow the manufacturer's product recommendations for pressurized steam handling.
WARNING: Cancer and Reproductive Harm- www.P65Warnings.ca.gov

2645 Executive Park Drive, Weston, Fort Lauderdale, FL 33331, EEUU
sales@kmxusa.us
www.kmxusa.us

ESPECIFICACIONES TÉCNICAS

Body Size	56mm
Female Thread	NPT
Female Thread Size	1"
Material	316 Stainless Steel
Maximum Operating Pressure	150 PSI
Maximum Temperature	350°F (177°C)
Factory Part Number	DDSC100SS
Seal	EPDM 291
Weight Lb	4.0000

KMX
2645 Executive Park Drive, Weston, Fort Lauderdale, FL 33331, EEUU
sales@kmxusa.us
www.kmxusa.us