DF-SERIES CARTRIDGE ELEMENTS- PES MEMBRANE



** Imágenes referenciales*
*** Algunas características pueden variar sin previo aviso, venta sujeta a stock disponible*

FECHA
: 11/23/2026 08:48 PM

SKU
: 11640

MARCA
: DIXON VALVE

MODELO
: DF-PESE7E6S

Specifications:
Maximum differential pressure: 45 PSID
Maximum operating pressure: 45 PSID
Cartridge Element Lengths: 10" to 40"
Micron ratings:.1,.22,.45,.60. 80, 1.2 and 5.0

Features:
FDA title 21 compliant
Cartridge elements are constructed in a clean room environment
Cartridge elements have excellent dirt holding capacity with low flow resistance
Cartridge elements are free of surfactants, resins, binders, and adhesives
Low protein binding and chemical compatibility
Naturally hydrophilic media does not need wetting before use

Construction:
Cartridge element: polethersulfone; core material: polypropylene
Gasket/O-Ring: Buna, FKM, PTFE, silicone, neoprene, and EPDM

Note:
All sizes are 6pcs/case and sold in case quantities only.
There are many more options, including industrial housing and cartridge elements. All cartridge elements are manufactured to industry standards and are interchangeable with other manufacturers' products. Please call Dixon Sanitary 800.789.1718 for further information.

Safety notes:
WARNING: Cancer and Reproductive Harm- www.P65Warnings.ca.gov

2645 Executive Park Drive, Weston, Fort Lauderdale, FL 33331, EEUU
sales@kmxusa.us
www.kmxusa.us

ESPECIFICACIONES TÉCNICAS

Cartridge Element Length	30"
Case	Case Qty: 6 pieces
Diameter	2.65" OD/ 1" Center ID
Material	Polyethersulfone/Polyproplyene/Silicone
Micron Rating	.22
Factory Part Number	DF-PESE7E6S
Style	Hard Cage/226/Fin
Weight Lb	10.0000

KMX

2645 Executive Park Drive, Weston, Fort Lauderdale, FL 33331, EEUU
sales@kmxusa.us

www.kmxusa.us