UL FUELMASTER DIESEL NOZZLE WITH SAFETY VALVE



** Imágenes referenciales*
*** Algunas características pueden variar sin previo aviso, venta sujeta a stock disponible*

FECHA
: 11/24/2026 12:22 AM

SKU
: 23887

MARCA
: DIXON VALVE

MODELO
: DFN100HF-NPNF

Applications:
Truck stops and terminal operations

Specifications:
UL listed for use with Gas 10% Ethanol blend and diesel

Features:
High flow capacity
Micro-touch valve provides smooth operation and exceptional flow control.
Roto-matic latch pin provides positive auto shut-off
Pure PTFE packing eliminates stem leaks
Super tough nylon hand guard
Easy to change 'locknut style' spout assembly
Green scruff guard
Trigger hold-open clip
No pressure, no flow' (NPNF) safety valve prevents the trigger from being held open in pressure is not present

Construction:
Body and spout: Aluminum
Body caps: Zinc
Seals: FKM
Poppet disk: FKM
Stem packing: PTFE
Handguard and trigger hold-open clip: Super tough nylon
Trigger: Steel
Snap-on cover: Plastic
Scuff guard: Vinyl

Safety notes:
Not designed for use with gravity flow tanks, small 12 volt pumps, AC utility

2645 Executive Park Drive, Weston, Fort Lauderdale, FL 33331, EEUU
sales@kmxusa.us
www.kmxusa.us

pumps, farm pumps or consumer pumps

WARNING: Cancer and Reproductive Harm- www.P65Warnings.ca.gov

ESPECIFICACIONES TÉCNICAS

Flow	35 GPM at 20 PSI
Inlet	1" female NPT
Intended Service	Diesel
Material	Aluminum
Outlet	1-3/16" spout
Factory Part Number	DFN100HF-NPNF
Weight Lb	4.0000