MANNTEK DRY GAS ADAPTER TANK UNIT X FEMALE ACME



** Imágenes referenciales*
*** Algunas características pueden variar sin previo aviso, venta sujeta a stock disponible*

FECHA
: 11/24/2026 01:37 AM

SKU
: 11701

MARCA
: DIXON VALVE

MODELO
: DGA100SS175

Applications:
Dry gas couplings are designed for safe loading and discharge of bobtails or intermediate bulk delivery trucks and transfer to and from railcars.
The primary application is in the handling of LPG- Propane and Butane.

Features:
Quick and easy to connect and can be connected to a hose unit with pressures up to 225 PSI
For higher pressure, couplings can easily be equipped with a pressure relief valve that dissipates trapped fluid pressure into the hose coupler without spillage.
Reliable- easy to use, easy to maintain and saves time
Minimizes the risk of cold burns, spillage and product loss, and health risks
Keeps the environment free of hazardous vapors and liquids

Construction:
Stainless steel and brass/gunmetal
Gunmetal is produced to U.S. government bronze specification G

Compatibility & Interchange Data:
Compatible with existing dry disconnect couplings

Safety notes:
Working pressure is based on PSI at ambient temperature 70°F, for pressure ratings at other temperatures contact Dixon.
WARNING: Cancer and Reproductive Harm- www.P65Warnings.ca.gov

2645 Executive Park Drive, Weston, Fort Lauderdale, FL 33331, EEUU
sales@kmxusa.us
www.kmxusa.us

ESPECIFICACIONES TÉCNICAS

Body Size	56 mm
Factory Part Number	DGA100SS175
Female Thread	ACME
Female Thread Size	1-3/4"
Material	316 Stainless Steel
Seal	FKM (FPM)
Weight Lb	1.9700
Working Pressure	360 PSI

KMX
2645 Executive Park Drive, Weston, Fort Lauderdale, FL 33331, EEUU
sales@kmxusa.us
www.kmxusa.us