FUELER 100? PLUS



** Imágenes referenciales*
*** Algunas características pueden variar sin previo aviso, venta sujeta a stock disponible*

FECHA
: 11/23/2026 06:04 PM

SKU
: 11922

MARCA
: DIXON VALVE

MODELO
: DNOG5PL

Applications
Designed for high-volume fuel transfer
Typical uses include high-volume truck fleet and bus terminals, fuel oil delivery, and industrial operations

Specifications
Inlet: 1-1/4" 1-1/2" NPT or BSPP
Spout: 1-3/8"
Weight: 6.9 lbs.
Length: 13.5"
Maximum working pressure: 100 PSI, 90 GPM

Features
Higher flow rate than standard fueling nozzles
High-strength aluminum body casting for great durability
Roto-matic latch pin for smooth automatic shut-off
PTFE stem packing eliminates leaks
Dual poppers for easy high-pressure operation
Grooved spout holds nozzle in the tank
Hand guard is integrated with the body
Nylon spout lock nut does not gall, making it easy to change the spout

Construction
Body: high-strength aluminum
Body cap: high-strength cast aluminum
Spout: aluminum
Lever: high-strength cast aluminum
Vacuum cap: zinc
Main stem: stainless steel
Seals: FKM/Nitrile
Packing: PTFE

2645 Executive Park Drive, Weston, Fort Lauderdale, FL 33331, EEUU
sales@kmxusa.us
www.kmxusa.us

Safety notes

WARNING: Cancer and Reproductive Harm- www.P65Warnings.ca.gov

ESPECIFICACIONES TÉCNICAS

Description	1-1/4" NPT inlet Hi-Flow PLUS fuel nozzle with 1-3/8 spout
Factory Part Number	DNOG5PL
Weight Lb	6.9000

KMX

2645 Executive Park Drive, Weston, Fort Lauderdale, FL 33331, EEUU

sales@kmxusa.us

www.kmxusa.us