DQC E-SERIES STRAIGHT THROUGH INTERCHANGE FEMALE PLUG

FECHA
: 11/23/2026 07:11 PM

SKU
: 12052

MARCA
: DIXON VALVE

MODELO
: E12F12-S





** Imágenes referenciales*
*** Algunas características pueden variar sin previo aviso, venta sujeta a stock disponible*

Features:
Straight-Through Pressure-Wash Interchange
Interchanges with Parker ST-Series, Foster FST-Series, Tomco Series-ST, Hansen ST-Series
These plugs have no internal valves, providing maximum flow with minimum pressure drop.

Construction:
Machined components are manufactured using 303 stainless steel bar stock

Safety notes:
Do Not Disconnect with pressure in line.
Dixon cannot assume liability for misapplication of products resulting in equipment down-time, lost production, property damage and/or personal injury including death.
WARNING: Cancer and Reproductive Harm- www.P65Warnings.ca.gov

ESPECIFICACIONES TÉCNICAS

Body Size	1-1/2"
Burst Pressure	8,000 PSI (552 Bar)
Factory Part Number	E12F12-S
Female Thread	NPTF
Female Thread Size	1-1/2"-11-1/2
Hex	2-1/4"
Length	2.74 (69.6mm)
Material	303 Stainless Steel

2645 Executive Park Drive, Weston, Fort Lauderdale, FL 33331, EEUU
sales@kmxusa.us
www.kmxusa.us

ESPECIFICACIONES TÉCNICAS

Maximum OD	2.60 (66.0mm)
Maximum Operating Pressure	2,000 PSI (138 Bar)
Weight Lb	1.1500

KMX
2645 Executive Park Drive, Weston, Fort Lauderdale, FL 33331, EEUU
sales@kmxusa.us
www.kmxusa.us