DQC E-SERIES STRAIGHT THROUGH INTERCHANGE FEMALE PLUG





** Imágenes referenciales*
*** Algunas características pueden variar sin previo aviso, venta sujeta a stock disponible*

FECHA
: 11/23/2026 06:53 PM

SKU
: 12055

MARCA
: DIXON VALVE

MODELO
: E16F16

Features:
Straight-Through Pressure-Wash Interchange
Interchanges with Parker ST-Series, Foster FST-Series, Tomco Series-ST, Hansen ST-Series
These plugs have no internal valves, providing maximum flow with minimum pressure drop.

Construction:
Machined components are manufactured using solid steel
Steel componentry is plated using ROHS Compliant Trivalent Chrome
Steel nipples are hardened to provide heavy duty performance.

Safety notes:
Do Not Disconnect with pressure in line.
Dixon cannot assume liability for misapplication of products resulting in equipment down-time, lost production, property damage and/or personal injury including death.
WARNING: Cancer and Reproductive Harm- www.P65Warnings.ca.gov

ESPECIFICACIONES TÉCNICAS

Body Size	2"
Burst Pressure	8,000 PSI (552 Bar)
Factory Part Number	E16F16
Female Thread	NPTF
Female Thread Size	2" - 11-1/2
Hex	2-5/8"
Length	3.00 (76.2mm)

2645 Executive Park Drive, Weston, Fort Lauderdale, FL 33331, EEUU
sales@kmxusa.us
www.kmxusa.us

ESPECIFICACIONES TÉCNICAS

Material	Steel
Maximum OD	3.03 (77.0mm)
Maximum Operating Pressure	2,000 PSI (138 Bar)
Weight Lb	1.9800

KMX

2645 Executive Park Drive, Weston, Fort Lauderdale, FL 33331, EEUU
sales@kmxusa.us

www.kmxusa.us