ALUMINUM MALE X FEMALE SWIVEL BUTTERFLY VALVE



** Imágenes referenciales*
*** Algunas características pueden variar sin previo aviso, venta sujeta a stock disponible*

FECHA
: 11/24/2026 02:29 AM

SKU
: 13526

MARCA
: DIXON VALVE

MODELO
: FMBTFLY40F45F

Applications:
This valve permits safe controlled flow to the intake pump and can be used in draft situations.

Use:
This unit can be used in either direction i.e.: inlet/outlet.

Features:
Hard anodized lightweight aluminum flanges provide a longer life span.

Construction:
Body wafer is lightweight aluminum cast 356-T6 with standard 10 position lever handle.
Comes furnished with a 3/4" push-pull drain valve.
Body of valve is ASTN A-126 cast iron
Buna seat
Finish hardcoat anodized cast aluminum bolt flanges- minimum thickness 0.001"

Note:
Lever handle to center valve is 10-1/4"

Safety notes:
WARNING: Cancer and Reproductive Harm- www.P65Warnings.ca.gov

2645 Executive Park Drive, Weston, Fort Lauderdale, FL 33331, EEUU
sales@kmxusa.us
www.kmxusa.us

ESPECIFICACIONES TÉCNICAS

Height	18.0"
Length	9.5"
Male Thread	NST (NH)
Male Thread Size	4"
Factory Part Number	FMBTFLY40F45F
Pressure Rating	185 PSI
Swivel Thread	NST (NH)
Swivel Thread Size	4-1/2"
Width	11.0"

KMX

2645 Executive Park Drive, Weston, Fort Lauderdale, FL 33331, EEUU
sales@kmxusa.us

www.kmxusa.us