ALUMINUM MALE X FEMALE SWIVEL BUTTERFLY VALVE



** Imágenes referenciales*
*** Algunas características pueden variar sin previo aviso, venta sujeta a stock disponible*

FECHA
: 11/24/2026 02:29 AM

SKU
: 13531

MARCA
: DIXON VALVE

MODELO
: FMBTFLY60F60F

Applications:
This valve permits safe controlled flow to the intake pump and can be used in draft situations.

Use:
This unit can be used in either direction i.e.: inlet/outlet.

Features:
Hard anodized lightweight aluminum flanges provide a longer life span.

Construction:
Body wafer is lightweight aluminum cast 356-T6 with standard 10 position lever handle.
Comes furnished with a 3/4" push-pull drain valve.
Body of valve is ASTN A-126 cast iron
Buna seat
Finish hardcoat anodized cast aluminum bolt flanges- minimum thickness 0.001"

Note:
Lever handle to center valve is 10-1/4"

Safety notes:
WARNING: Cancer and Reproductive Harm- www.P65Warnings.ca.gov

2645 Executive Park Drive, Weston, Fort Lauderdale, FL 33331, EEUU
sales@kmxusa.us
www.kmxusa.us

ESPECIFICACIONES TÉCNICAS

Height	18.0"
Length	9.5"
Male Thread	NST (NH)
Male Thread Size	6"
Factory Part Number	FMBTFLY60F60F
Pressure Rating	185 PSI
Swivel Thread	NST (NH)
Swivel Thread Size	6"
Weight Lb	39.0000
Width	11.0"

KMX

2645 Executive Park Drive, Weston, Fort Lauderdale, FL 33331, EEUU
sales@kmxusa.us

www.kmxusa.us