ALUMINUM 2-WAY BALL VALVE FEMALE SWIVEL INLET



** Imágenes referenciales*
*** Algunas características pueden variar sin previo aviso, venta sujeta a stock disponible*

FECHA
: 11/24/2026 02:17 AM

SKU
: 13537

MARCA
: DIXON VALVE

MODELO
: FMBV45F25F

Applications:
This valve will feed two smaller attack lines from one large diameter supply line. The 2-1/2" outlet is a gated ball valve resulting in a safe controlled flow of water.

Use:
Can be used to distribute water in the opposite direction

Construction:
High strength aluminum alloy, 356-T6
Finish hardcoat anodized- minimum thickness 0.001"
Comes complete with a carrying handle.

Available Options:
Consult Dixon for pricing and availability of other thread options.

Safety notes:
WARNING: Cancer and Reproductive Harm- www.P65Warnings.ca.gov

ESPECIFICACIONES TÉCNICAS

Inlet	4-1/2" female swivel NST (NH)
Material	Aluminum
Outlet	(2) 2-1/2" male NST (NH)
Factory Part Number	FMBV45F25F
Working Pressure	280 PSI

2645 Executive Park Drive, Weston, Fort Lauderdale, FL 33331, EEUU
sales@kmxusa.us
www.kmxusa.us