PISTON INTAKE FEMALE SWIVEL X MALE WITH RELIEF VALVE



** Imágenes referenciales*
*** Algunas características pueden variar sin previo aviso, venta sujeta a stock disponible*

FECHA
: 11/24/2026 01:12 AM

SKU
: 13568

MARCA
: DIXON VALVE

MODELO
: FMGR60F60F

Applications:
Valve permits safe controlled flow to the intake pump and can also be used to draft.

Features:
Relief valve- double spring, cartridge type, adjustable from 50 to 200 PSI

Construction:
High strength aluminum alloy, 356-T6
Finish hardcoat anodized throughout- minimum thickness 0.001"
The valve is complete with a 30° elbow (permitting smoother water flow), adjustable relief valve, retractable knob on hand wheel and air bleed off.

Safety notes:
WARNING: Cancer and Reproductive Harm- www.P65Warnings.ca.gov

ESPECIFICACIONES TÉCNICAS

Female Thread	NST (NH) swivel
Female Thread Size	(2) 6"
Height	17.0"
Length	12.0"
Male Thread	NST (NH)
Male Thread Size	6"
Material	Aluminum
Maximum Operating Pressure	280 PSI
Factory Part Number	FMGR60F60F

2645 Executive Park Drive, Weston, Fort Lauderdale, FL 33331, EEUU
sales@kmxusa.us
www.kmxusa.us

ESPECIFICACIONES TÉCNICAS

Width	8.0"

KMX

2645 Executive Park Drive, Weston, Fort Lauderdale, FL 33331, EEUU

sales@kmxusa.us

www.kmxusa.us