WELDING GAUGE



** Imágenes referenciales*
*** Algunas características pueden variar sin previo aviso, venta sujeta a stock disponible*

FECHA
: 11/23/2026 08:34 PM

SKU
: 14579

MARCA
: DIXON VALVE

MODELO
: GBRW30

Applications:
All of the gauges supplied by Dixon are designed for long, reliable service under rugged conditions. Typical applications include those on pumps, hydraulic and pneumatic systems, compressors, machine tools and many other installations where it is necessary to have a gauge with a non-corrosive movement.

Specifications:
± 3-2-3% accuracy according to ASME B40.100 Grade B

Construction:
Copper alloy bourdon tube
"USE NO OIL" written in red on face
Stainless steel case
Twist-lock polycarbonate window
Copper alloy bourdon tube

Safety notes:
WARNING: Cancer and Reproductive Harm- www.P65Warnings.ca.gov

ESPECIFICACIONES TÉCNICAS

Factory Part Number	GBRW30
Figure Interval	5
Material	Brass
Minor Gradient	.5
Mount	1/4" lower mount
Pressure Range	0-30 PSI

2645 Executive Park Drive, Weston, Fort Lauderdale, FL 33331, EEUU
sales@kmxusa.us
www.kmxusa.us

ESPECIFICACIONES TÉCNICAS

Size	2-1/2" Face
Temperature Range	-40°F to 140°F (-40°C to 60°C)
Weight Lb	0.4380

KMX
2645 Executive Park Drive, Weston, Fort Lauderdale, FL 33331, EEUU
sales@kmxusa.us
www.kmxusa.us