# ABS STANDARD DRY GAUGE CENTER BACK MOUNT




** Imágenes referenciales*
*** Algunas características pueden variar sin previo aviso, venta sujeta a stock disponible*

FECHA
: 11/23/2026 11:44 PM

SKU
: 14588

MARCA
: DIXON VALVE

MODELO
: GC215

Applications:
All of the gauges supplied by Dixon are designed for long, reliable service under rugged conditions. Typical applications include those on pumps, hydraulic and pneumatic systems, compressors, machine tools and many other installations where it is necessary to have a gauge with a non-corrosive movement.

Specifications:
ASME B40.1, Grade B (± 3-2-3% accuracy)

Features:
PowerFlex™ movement with polyester segment, designed to resist the effects of shock, vibration and pulsation.

Construction:
Polycarbonate window
Black aluminum pointer
ABS plastic case, corrosion resistant
C-shaped bronze safety bourdon tube
Center back mount

Safety notes:
WARNING: Cancer and Reproductive Harm- www.P65Warnings.ca.gov



2645 Executive Park Drive, Weston, Fort Lauderdale, FL 33331, EEUU
sales@kmxusa.us
www.kmxusa.us

## ESPECIFICACIONES TÉCNICAS

| | |
|---|---|
| **Factory Part Number** | GC215 |
| **Figure Interval** | 5 |
| **Minor Gradient** | .5 |
| **Mount** | 1/4" |
| **Pressure Range** | 0-30 PSI |
| **Size** | 2" Face |
| **Temperature Range** | -40°F to 150°F (-40°C to 65.6°C) |
| **Weight Lb** | 0.1900 |



KMX

2645 Executive Park Drive, Weston, Fort Lauderdale, FL 33331, EEUU

sales@kmxusa.us

www.kmxusa.us