COMPOUND GAUGE LOWER MOUNT



** Imágenes referenciales*
*** Algunas características pueden variar sin previo aviso, venta sujeta a stock disponible*

FECHA
: 11/23/2026 05:58 PM

SKU
: 14692

MARCA
: DIXON VALVE

MODELO
: GL315

Applications:
All of the gauges supplied by Dixon are designed for long, reliable service under rugged conditions. Typical applications include those on pumps, hydraulic and pneumatic systems, compressors, machine tools and many other installations where it is necessary to have a gauge with a non-corrosive movement.

Specifications:
ASME B40.1, Grade B accuracy (± 3-2-3 % accuracy)
30" Mercury (Hg)

Features:
PowerFlex™ movement with polyester segment, designed for extended wear

Construction:
ABS plastic case, corrosion resistant
Bronze bourdon tube / brass socket
Polycarbonate window
Black aluminum pointer

Safety notes:
WARNING: Cancer and Reproductive Harm- www.P65Warnings.ca.gov

2645 Executive Park Drive, Weston, Fort Lauderdale, FL 33331, EEUU
sales@kmxusa.us
www.kmxusa.us

ESPECIFICACIONES TÉCNICAS

Factory Part Number	GL315
Figure Interval	30/20 (Hg/PSI)
Minor Gradient	10/10 (Hg/PSI)
Mount	1/4" Lower Mount
Pressure Range	0-200 PSI
Size	2-1/2" Face
Temperature Range	-40°F to 150°F (-40°C to 65.6°C)
Weight Lb	0.2450

KMX
2645 Executive Park Drive, Weston, Fort Lauderdale, FL 33331, EEUU
sales@kmxusa.us
www.kmxusa.us