FLUTTERGUARD? DRY GAUGE



** Imágenes referenciales*
*** Algunas características pueden variar sin previo aviso, venta sujeta a stock disponible*

FECHA
: 11/23/2026 05:43 PM

SKU
: 14700

MARCA
: DIXON VALVE

MODELO
: GL335FG

Applications:
All of the gauges supplied by Dixon are designed for long, reliable service under rugged conditions. Typical applications include those on pumps, hydraulic and pneumatic systems, compressors, machine tools and many other installations where it is necessary to have a gauge with a non-corrosive movement.

Specifications:
ASME B40.1, Grade B (± 3-2-3% accuracy)

Features:
FlutterGuard™ virtually eliminates pointer flutter, making the gauge easier to read and reducing excessive movement wear. Liquid-free casing results in lighter weight and eliminates the chance of gauge leakage.
PowerFlex™ movement with polyester segment, designed to resist the effects of shock, vibration and pulsation.

Construction:
ABS plastic case, corrosion resistant
C-shaped bronze safety bourdon tube (600 PSI and lower)
Polycarbonate window
Black aluminum pointer

Safety notes:
WARNING: Cancer and Reproductive Harm- www.P65Warnings.ca.gov

2645 Executive Park Drive, Weston, Fort Lauderdale, FL 33331, EEUU
sales@kmxusa.us
www.kmxusa.us

ESPECIFICACIONES TÉCNICAS

Factory Part Number	GL335FG
Figure Interval	20
Minor Gradient	5
Mount	1/4" Lower Mount
Pressure Range	0-160 PSI
Size	2-1/2" Face
Temperature Range	-40°F to 150°F (-40°C to 65.6°C)
Weight Lb	0.2230

KMX
2645 Executive Park Drive, Weston, Fort Lauderdale, FL 33331, EEUU
sales@kmxusa.us
www.kmxusa.us