BRASS LIQUID FILLED GAUGE LOWER MOUNT



** Imágenes referenciales*
*** Algunas características pueden variar sin previo aviso, venta sujeta a stock disponible*

FECHA
: 11/23/2026 08:18 PM

SKU
: 14742

MARCA
: DIXON VALVE

MODELO
: GLBR5000

Applications:
All of the gauges supplied by Dixon are designed for long, reliable service under rugged conditions. Typical applications include those on pumps, hydraulic and pneumatic systems, compressors, machine tools and many other installations where it is necessary to have a gauge with a non-corrosive movement.

Specifications:
± 2-1-2% accuracy

Construction:
Glycerin filled
Solid cast brass case with ABS cover ring
Acrylic window with membrane assembly
Copper alloy bourdon tube
Brass movement with highly polished bearing surfaces

Safety notes:
WARNING: Cancer and Reproductive Harm- www.P65Warnings.ca.gov

2645 Executive Park Drive, Weston, Fort Lauderdale, FL 33331, EEUU
sales@kmxusa.us
www.kmxusa.us

ESPECIFICACIONES TÉCNICAS

Factory Part Number	GLBR5000
Figure Interval	1000
Material	Brass
Minor Gradient	100
Mount	1/4"
Pressure Range	0-5000 PSI
Size	2-1/2" Face
Temperature Range	-4°F to 140°F (-20°C to 60°C)
Weight Lb	0.8100

KMX
2645 Executive Park Drive, Weston, Fort Lauderdale, FL 33331, EEUU
sales@kmxusa.us
www.kmxusa.us