
# DQC H-SERIES ISO-B HIGH VOLUME FEMALE PLUG





FECHA
: 11/24/2026 12:06 AM

SKU
: 24453

MARCA
: DIXON VALVE

MODELO
: H10F10-SS

Construction:
Machined components are manufactured using solid bar stock
Stainless steel balls, retaining rings and springs maximize corrosion resistance and extend service life.

Available Options:
Contact Dixon for all available option adders

Compatibility & Interchange Data:
Interchangeable to ISO7241 Series 'B'
Parker 60-Series, Snap-Tite 72-Series, Hansen HK-Series, Faster Series 'HNV', Aeroquip/Eaton FD45, Stucchi Series IRB/IRBO/IRBX

Safety notes:
WARNING: Cancer and Reproductive Harm- www.P65Warnings.ca.gov

## ESPECIFICACIONES TÉCNICAS

| | |
|---|---|
| **Body Size** | 1-1/4" |
| **Burst Pressure** | 8500 PSI (580 bar) |
| **Factory Part Number** | H10F10-SS |
| **Hex** | 2-3/8" |
| **Length** | 4.25" (108.0mm) |
| **Material** | 316 Stainless Steel |
| **Maximum OD** | 2.60" (66.0mm) |
| **Maximum Operating Pressure** | 1000 PSI (70 bar) |
| **Temperature Range** | -40°F to +250°F (-40°C to +121°C) |

** Imágenes referenciales*
*** Algunas características pueden variar sin previo aviso, venta sujeta a stock disponible*



2645 Executive Park Drive, Weston, Fort Lauderdale, FL 33331, EEUU
sales@kmxusa.us
www.kmxusa.us

## ESPECIFICACIONES TÉCNICAS

| | |
|---|---|
| **Thread** | Female NPTF |
| **Thread Size** | 1-1/4" - 11-1/2 |
| **Weight Lb** | 2.1900 |



KMX
2645 Executive Park Drive, Weston, Fort Lauderdale, FL 33331, EEUU
sales@kmxusa.us
www.kmxusa.us