PERMANENT PUMP HOSE COUPLING



** Imágenes referenciales*
*** Algunas características pueden variar sin previo aviso, venta sujeta a stock disponible*

FECHA
: 11/23/2026 05:40 PM

SKU
: 27535

MARCA
: DIXON VALVE

MODELO
: H5752

Applications:
Economical and trouble-free
Specifications:
UL Approved
Features:
Serrations on the stem become imbedded in the hose eliminating wicking and leakage.
The shell extends beyond the stem to prevent cutting of interior walls.
Tapered ends of stem and shell protect hose when flexed.
Couplings provide tamper-proof static connection which cannot be broken without completely damaging coupling and hose.
Internal expansion of stem to nominal ID of hose provides full flow
Broad, firm grip of coupling extends hose life by making it possible for hose to withstand more flexing.
Note:
Hand and electrically operated installation equipment is available. Consult Dixon for pricing and availability.
Safety notes:
Reattach static wire if required.
Hose service working pressure (including surges and spikes) is never to exceed the maximum recommended working pressure for the fitting. The assembly\'s (hose + coupling) maximum working pressure is the lesser of the hose rated working pressure or the coupling rated working pressure.
WARNING: Cancer and Reproductive Harm- www.P65Warnings.ca.gov

2645 Executive Park Drive, Weston, Fort Lauderdale, FL 33331, EEUU
sales@kmxusa.us
www.kmxusa.us

ESPECIFICACIONES TÉCNICAS

Hose ID	3/4"
Hose OD	1-11/64"
Material	Chrome Plated Brass
Factory Part Number	H5752
Thread	NPT
Thread Size	3/4"
Weight Lb	0.2600

KMX

2645 Executive Park Drive, Weston, Fort Lauderdale, FL 33331, EEUU
sales@kmxusa.us

www.kmxusa.us