# DUBL-GRIP® FIELD ATTACHABLE COUPLING FOR CURB PUMP HOSE



** Imágenes referenciales*
*** Algunas características pueden variar sin previo aviso, venta sujeta a stock disponible*

FECHA
: 11/23/2026 11:31 PM

SKU
: 24575

MARCA
: DIXON VALVE

MODELO
: H605

Specifications:
UL recognized
Fluid Hose number MH49909

Features:
Two-piece field attachable coupling
Streamlined design prevents damage to hose and fits well on new pump equipment.
Wide, flat surfaces of body threads protect inside of hose from breaking.
Tapered surfaces of sleeve and body cradle hose, prevent one-point strain from flexing.
Hose is gripped on its full circumference in two places, ensuring a rigid leak-proof connection.
Couplings have standard male NPT threads

Installation
Easy assembly: hose is held in position by sleeve as body is threaded home, only a wrench is required to assemble the Dubl-Grip®.

Safety notes:
Reattach static wire if required.
Hose service working pressure (including surges and spikes) is never to exceed the maximum recommended working pressure for the fitting. The assembly's (hose + coupling) maximum working pressure is the lesser of the hose rated working pressure or the coupling rated working pressure.
WARNING: Cancer and Reproductive Harm- www.P65Warnings.ca.gov



2645 Executive Park Drive, Weston, Fort Lauderdale, FL 33331, EEUU
sales@kmxusa.us
www.kmxusa.us

## ESPECIFICACIONES TÉCNICAS

| | |
|---|---|
| **Factory Part Number** | H605 |
| **Hose ID** | 3/4" |
| **Hose OD** | 1-1/4" |
| **Material** | Chrome Plated Brass |
| **Thread** | NPT |
| **Thread Size** | 3/4" |
| **Weight Lb** | 0.5000 |



KMX

2645 Executive Park Drive, Weston, Fort Lauderdale, FL 33331, EEUU

sales@kmxusa.us

www.kmxusa.us