NITRILE COVERED FIRE HOSE HEAVY DUTY



FECHA
: 11/23/2026 10:17 PM

SKU
: 14971

MARCA
: DIXON VALVE

MODELO
: H610Y50RAS

Applications:
Ideal for heavy-duty washdown, refineries and power plants

Construction:
Outer: Yellow, Thick Ribbed Nitrile
Tube: Nitrile

Safety notes:
Under no circumstance should the hose be used beyond the working pressure of the fittings to which it is coupled.
Assembled hose should be hydrostatically proof tested before use, and thereafter in accordance with NFPA 1962.
WARNING: Cancer and Reproductive Harm- www.P65Warnings.ca.gov

** Imágenes referenciales*
*** Algunas características pueden variar sin previo aviso, venta sujeta a stock disponible*

ESPECIFICACIONES TÉCNICAS

Bowl Size	1-1/4"
Color	Yellow
Coupling Type	Aluminum Expansion Ring, Rocker Lug
Factory Part Number	H610Y50RAS
Hose Size	1"
Proof Pressure	600 PSI
Service Test Pressure	300 PSI
Thread	NPSH
Weight Lb	8.7800
Working Pressure	270 PSI

2645 Executive Park Drive, Weston, Fort Lauderdale, FL 33331, EEUU
sales@kmxusa.us
www.kmxusa.us

ESPECIFICACIONES TÉCNICAS

KMX
2645 Executive Park Drive, Weston, Fort Lauderdale, FL 33331, EEUU
sales@kmxusa.us
www.kmxusa.us