NITRILE COVERED FIRE HOSE HEAVY DUTY



** Imágenes referenciales*
*** Algunas características pueden variar sin previo aviso, venta sujeta a stock disponible*

FECHA
: 11/23/2026 09:45 PM

SKU
: 14983

MARCA
: DIXON VALVE

MODELO
: H625Y50UC

Applications:
Ideal for heavy-duty washdown, refineries and power plants

Construction:
Outer: Yellow, Thick Ribbed Nitrile
Tube: Nitrile

Safety notes:
Under no circumstance should the hose be used beyond the working pressure of the fittings to which it is coupled.
Assembled hose should be hydrostatically proof tested before use, and thereafter in accordance with NFPA 1962.
WARNING: Cancer and Reproductive Harm- www.P65Warnings.ca.gov

ESPECIFICACIONES TÉCNICAS

Bowl Size	2-13/16"
Color	Yellow
Coupling Type	Uncoupled
Factory Part Number	H625Y50UC
Hose Size	2-1/2"
Proof Pressure	600 PSI
Service Test Pressure	300 PSI
Weight Lb	28.0000
Working Pressure	270 PSI

2645 Executive Park Drive, Weston, Fort Lauderdale, FL 33331, EEUU
sales@kmxusa.us
www.kmxusa.us