# H8 SERIES FORGED BELLOWS SEAL GATE VALVE



** Imágenes referenciales*
*** Algunas características pueden variar sin previo aviso, venta sujeta a stock disponible*

FECHA
: 11/24/2026 12:19 AM

SKU
: 27543

MARCA
: DIXON VALVE

MODELO
: H8CSW100

Applications:
For use in applications where leakage into or out of the valve is unacceptable such as heat transfer oil, toxic fluids, steam and regulated media.
Our bellows technology keeps corrosive or harmful atmospheric conditions from entering the process.
Specifications:
ANSI/API Class 150-800 available
Valve tested to ASME B16.34 / API 598
Meets MSS SP-117
5-year bellow warranty
Assembled and tested in a US ISO 9001:2015 certified facility
Features:
Stainless steel bellows (Inconel™ bellows available) provides longer life and maximum corrosion resistance
Zero stem leakage eliminates media loss and satisfies environmental regulations
Zero maintenance results in lower operating costs / no downtime
Reduce monitoring costs
Construction:
Three stem seals for safety: metallic bellows, graphite packing, backseat in open position
Hardfaced Stellite® 6 seating surface provides long life
Welded bonnet
Socket weld
Available Options:
Additional alloys, trims, end configurations and sizes are available, contact Dixon for details.
Inconel® 625 bellows
Note:
Stellite™ is a registered trademark of Thermadyne.
Inconel™ is a trademark of Huntington Alloys, inc.



2645 Executive Park Drive, Weston, Fort Lauderdale, FL 33331, EEUU
sales@kmxusa.us
www.kmxusa.us

Safety notes:

WARNING: Cancer and Reproductive Harm- www.P65Warnings.ca.gov

Dixon recommends that all valve assemblies be tested in accordance with ASME and API recommendations and be inspected regularly to ensure that their use remains appropriate and that they are not damaged.

At no charge, Dixon is available to consult, train and recommend the proper selection and application of all valves we sell. We strongly recommend that distributers and end users make use of Dixon\'s Testing and Recommendation Services. Call 800.355.1991 to learn more.

WARNING: Cancer and Reproductive Harm- www.P65Warnings.ca.gov

## ESPECIFICACIONES TÉCNICAS

| | |
|---|---|
| **Body Pressure Class** | CL 800 |
| **Material** | A105 carbon steel |
| **Factory Part Number** | H8CSW100 |
| **Size** | 1" |
| **Type** | Gate, forged, welded bonnet |
| **Weight Lb** | 11.5000 |