HOLEDALL® DIN EXTERNAL CRIMP FEMALE STEM



** Imágenes referenciales*
*** Algunas características pueden variar sin previo aviso, venta sujeta a stock disponible*

FECHA
: 11/23/2026 10:30 PM

SKU
: 24609

MARCA
: DIXON VALVE

MODELO
: HA0242

Applications:
Recommended for food, dairy and pharmaceutical applications where increased flow capacity is important.

Note:
All stems are manufactured to suit inch bore hoses (not metric bore hoses)

Safety notes:
Holedall sanitary crimp stems are only to be used with Holedall sanitary stainless steel crimp ferrules
Holedall couplings, regardless of coupling style, are never to be used for steam service at any pressure.
Holedall fittings are not to be used with cable reinforced high-pressure hose, 4 or 6 braid wire hydraulic hose or any other service not listed in the recommendations. Consult Dixon for recommendations on usage.
Hose service working pressure (including surges and spikes) is never to exceed the maximum recommended working pressure for the fitting. The assembly's (hose + coupling) maximum working pressure is the lesser of the hose rated working pressure or the coupling rated working pressure.
Media being transported through the hose should be compatible with the stem material. Compatibility of ferrule material with the environment in which it will be used is recommended. Consult the Compatibility Chart or the Dixon factory for material compatibility.
For applications other than the ones list, please consult Dixon.
WARNING: Cancer and Reproductive Harm- www.P65Warnings.ca.gov

2645 Executive Park Drive, Weston, Fort Lauderdale, FL 33331, EEUU
sales@kmxusa.us
www.kmxusa.us

ESPECIFICACIONES TÉCNICAS

DN Size	65
Factory Part Number	HA0242
Material	316 Stainless Steel
Size	2-1/2"
Weight Lb	1.4400

KMX

2645 Executive Park Drive, Weston, Fort Lauderdale, FL 33331, EEUU

sales@kmxusa.us

www.kmxusa.us