DQC HS-SERIES ISO-B STEAM INTERCHANGE FEMALE PLUG





** Imágenes referenciales*
*** Algunas características pueden variar sin previo aviso, venta sujeta a stock disponible*

FECHA
: 11/23/2026 11:02 PM

SKU
: 24655

MARCA
: DIXON VALVE

MODELO
: HS6F6-S

Applications:
Designed exclusively for steam applications

Construction:
Machined components are manufactured using solid bar stock
Stainless steel balls, retaining rings and springs maximize corrosion resistance and extend service life.
Special high-temp EPDM O-rings designed for steam service

Compatibility & Interchange Data:
Interchangeable to ISO7241 Series 'B'
Parker 60-Series Steam Couplings

Safety notes:
Maximum working pressure has been calculated using standard saturated steam at 194°C (382°F) for general purpose continuous service. For advanced operating pressure or super-heated steam applications, contact Dixon for further information.
Warning: Do not disconnect under pressure!
WARNING: Cancer and Reproductive Harm- www.P65Warnings.ca.gov

2645 Executive Park Drive, Weston, Fort Lauderdale, FL 33331, EEUU
sales@kmxusa.us
www.kmxusa.us

ESPECIFICACIONES TÉCNICAS

Body Size	3/4"
Factory Part Number	HS6F6-S
Hex	1-5/16"
Length	2.43" (61.7mm)
Material	303 Stainless Steel
Maximum OD	1.44" (36.6mm)
Pressure Rating	Rated to 200 PSI gauge saturated steam 382°F (194°C)
Temperature Range	-70°F to +400°F (-57°C to +204°C)
Thread	Female NPTF
Thread Size	3/4"-14
Weight Lb	0.4600

KMX
2645 Executive Park Drive, Weston, Fort Lauderdale, FL 33331, EEUU
sales@kmxusa.us
www.kmxusa.us