HAMMER UNION 206 SERIES





** Imágenes referenciales*
*** Algunas características pueden variar sin previo aviso, venta sujeta a stock disponible*

FECHA
: 11/23/2026 11:32 PM

SKU
: 15770

MARCA
: DIXON VALVE

MODELO
: HU206250

Use:
Used in general service applications running air, water, oil or gas up to 2,000 PSI NSCWP (non-shock cold working pressure)

Features:
Nitrile O-ring mounted sub provides excellent sealing properties

Construction:
Grey sub, blue nut

Safety notes:
Hammer unions work at extremely high pressures. Mismatching components of one series with another (i.e. series 602 with series 1502) can lead to destruction of property, serious bodily injury or death.
Pressure rating given at ambient temperature 70°F/21°C.
WARNING: Cancer and Reproductive Harm- www.P65Warnings.ca.gov

ESPECIFICACIONES TÉCNICAS

Factory Part Number	HU206250
Material	Forged Steel
Maximum Operating Pressure	2000 PSI NSCWP
Size	2-1/2"
Style	Threaded
Temperature Range	-20°F to 250°F (-29°C to 121°C)
Weight Lb	10.5000

2645 Executive Park Drive, Weston, Fort Lauderdale, FL 33331, EEUU
sales@kmxusa.us
www.kmxusa.us