HAMMER UNION 602 SERIES

FECHA
: 11/23/2026 11:42 PM

SKU
: 15784

MARCA
: DIXON VALVE

MODELO
: HU602200BW





Use:
For use in mud, manifold service and truck mounting applications running water, oil or mud up to 6,000 PSI NSCWP (non-shock cold working pressure)

Features:
Lip type seal ring minimizes fluid flow turbulence while creating a pressure seal

Safety notes:
Hammer unions work at extremely high pressures. Mismatching components of one series with another (i.e. series 602 with series 1502) can lead to destruction of property, serious bodily injury or death.
Pressure rating given at ambient temperature 70°F/21°C.
WARNING: Cancer and Reproductive Harm- www.P65Warnings.ca.gov

** Imágenes referenciales*
*** Algunas características pueden variar sin previo aviso, venta sujeta a stock disponible*

ESPECIFICACIONES TÉCNICAS

Factory Part Number	HU602200BW
Material	Forged Steel, Schedule 80
Maximum Operating Pressure	6000 PSI NSCWP
Size	2"
Style	Buttweld
Temperature Range	-20°F to 250°F (-29°C to 121°C)
Weight Lb	16.0000

2645 Executive Park Drive, Weston, Fort Lauderdale, FL 33331, EEUU
sales@kmxusa.us
www.kmxusa.us