# DIXON® MALE FRAC FITTING WITH NUT



** Imágenes referenciales*
*** Algunas características pueden variar sin previo aviso, venta sujeta a stock disponible*

FECHA
: 11/23/2026 09:27 PM

SKU
: 15813

MARCA
: DIXON VALVE

MODELO
: HUM206300CS

Applications:
Used in the fast paced transfer of water and sand slurry at hydraulic fracturing sites.

Use:
Designed to work with Dixon King Crimp Sleeves or Ferrules.

Features:
One-piece design eliminates leak path experienced with two-piece threaded systems
Long lasting and dependable forged hammer nut
Durable and safe with reliable hose retention when crimped as specified

Construction:
Frac fittings: machined iron to ASTM standards; zinc plated
Nut: forged steel meeting AISI standards
Buna-N O-ring (O238BU)
Figures 100 and 200 have a metal-to-metal sealing surface; Figure 206 is similar to Figure 200 with a secondary seal to supplement the metal-to-metal design.

Compatibility & Interchange Data:
Interchangeable with current fittings; phase them into your current operation

Safety notes:
400 PSI working pressure with a minimum 4:1 safety factor (hose burst: hose working pressure) is only achieved with: 3" sizes uses standard crimp stem
WARNING: Cancer and Reproductive Harm- www.P65Warnings.ca.gov



2645 Executive Park Drive, Weston, Fort Lauderdale, FL 33331, EEUU
sales@kmxusa.us
www.kmxusa.us

## ESPECIFICACIONES TÉCNICAS

| | |
|---|---|
| **Description** | Male fitting |
| **Factory Part Number** | HUM206300CS |
| **Includes** | Nut,<br/>O-ring |
| **Mandatory Pkg/Box Qty** | 1 |
| **Material** | Forged steel nut,<br/>Iron fitting |
| **Seal** | Buna-N |
| **Size** | 3" |
| **Style** | Figure 206 |
| **Weight Lb** | 12.8000 |
| **Working Pressure** | 400 PSI at 70°F (21°C) |



KMX

2645 Executive Park Drive, Weston, Fort Lauderdale, FL 33331, EEUU

sales@kmxusa.us

www.kmxusa.us