CIP INTERNAL EXPANSION (IX) SANITARY STYLE CLAMP END STEM



** Imágenes referenciales*
*** Algunas características pueden variar sin previo aviso, venta sujeta a stock disponible*

FECHA
: 11/23/2026 11:35 PM

SKU
: 24783

MARCA
: DIXON VALVE

MODELO
: IXSE32-3A

Applications:
Flow Chief Sanitary Fittings are used in the food, dairy and beverage industries, recommended where increased flow capacity is important.

Specifications:
3A compliant when assembled by 3A authorized hose shop
Clean-In-Place (CIP) compliant

Note:
Special plug is required to expand CIP compliant fittings
Special adapter plate is required to expand 1-1/2" CIP compliant fittings
Consult maximum working pressure chart or contact Dixon for additional application and working pressure information.

Safety notes:
Flow Chief internal expansion (IX) fittings are only to be used with Flow Chief stainless steel ferrules
Holedall couplings, regardless of coupling style, are never to be used for steam service at any pressure.
Holedall fittings are not to be used with cable reinforced high-pressure hose, 4 or 6 braid wire hydraulic hose or any other service not listed in the recommendations. Consult Dixon for recommendations on usage.
Strict adherence to ferrule OD range (internally expanded) for each hose end to be assembled is essential for satisfactory performance.
Hose service working pressure (including surges and spikes) is never to exceed the maximum recommended working pressure for the fitting. The assembly's (hose + coupling) maximum working pressure is the lesser of the hose rated working pressure or the coupling rated working pressure.
Media being transported through the hose should be compatible with the stem material. Compatibility of ferrule material with the environment in which it will be used is recommended. Consult the Compatibility Chart or the Dixon factory

2645 Executive Park Drive, Weston, Fort Lauderdale, FL 33331, EEUU
sales@kmxusa.us
www.kmxusa.us

for material compatibility.

For applications other than the ones list, please consult Dixon.

WARNING: Cancer and Reproductive Harm- www.P65Warnings.ca.gov

ESPECIFICACIONES TÉCNICAS

Factory Part Number	IXSE32-3A
Material	304 Stainless Steel
Size	2"
Style	Internal Expansion
Weight Lb	1.3600

2645 Executive Park Drive, Weston, Fort Lauderdale, FL 33331, EEUU
sales@kmxusa.us
www.kmxusa.us