
DQC K-SERIES ISO-A INTERCHANGE FEMALE PLUG





** Imágenes referenciales*
*** Algunas características pueden variar sin previo aviso, venta sujeta a stock disponible*

FECHA
: 11/23/2026 11:07 PM

SKU
: 24818

MARCA
: DIXON VALVE

MODELO
: K12BF12

Features:
Poppet style shut-off valve

Construction:
Machined components are manufactured using solid bar stock
Stainless steel balls, retaining rings and springs maximize corrosion resistance and extend service life.
Steel componentry is plated using ROHS Compliant Trivalent Chrome.
Steel nipples are hardened to provide heavy duty performance and resist brinelling.

Available Options:
Contact Dixon for all available option adders
Oxy-Clean treatment is available

Compatibility & Interchange Data:
Interchangeable to ISO7241 Series 'A'
Parker 6600-Series, Aeroquip/Eaton FD56 (5600)
Faster ANV, Hansen HA 15000, Safeway S56-Series

Safety notes:
WARNING: Cancer and Reproductive Harm- www.P65Warnings.ca.gov

2645 Executive Park Drive, Weston, Fort Lauderdale, FL 33331, EEUU
sales@kmxusa.us
www.kmxusa.us

ESPECIFICACIONES TÉCNICAS

Body Size	1-1/2"
Burst Pressure	12600 PSI (850 bar)
Factory Part Number	K12BF12
Hex	2-3/8"
Length	3.29" (83.5mm)
Material	Steel
Maximum OD	2.74" (69.6mm)
Maximum Operating Pressure	3000 PSI (200 bar)
Temperature Range	-40°F to +250°F (-40°C to +121°C)
Thread	Female BSPP
Thread Size	1-1/2"-11
Weight Lb	2.0500

KMX
2645 Executive Park Drive, Weston, Fort Lauderdale, FL 33331, EEUU
sales@kmxusa.us
www.kmxusa.us