
DQC K-SERIES ISO-A INTERCHANGE FEMALE PLUG





** Imágenes referenciales*
*** Algunas características pueden variar sin previo aviso, venta sujeta a stock disponible*

FECHA
: 11/23/2026 09:32 PM

SKU
: 24848

MARCA
: DIXON VALVE

MODELO
: K6F6

Features:
Poppet style shut-off valve

Construction:
Machined components are manufactured using solid bar stock
Stainless steel balls, retaining rings and springs maximize corrosion resistance and extend service life.
Steel componentry is plated using ROHS Compliant Trivalent Chrome.
Steel nipples are hardened to provide heavy duty performance and resist brinelling.

Available Options:
Contact Dixon for all available option adders
Oxy-Clean treatment is available

Compatibility & Interchange Data:
Interchangeable to ISO7241 Series 'A'
Parker 6600-Series, Aeroquip/Eaton FD56 (5600)
Faster ANV, Hansen HA 15000, Safeway S56-Series

Safety notes:
WARNING: Cancer and Reproductive Harm- www.P65Warnings.ca.gov

2645 Executive Park Drive, Weston, Fort Lauderdale, FL 33331, EEUU
sales@kmxusa.us
www.kmxusa.us

ESPECIFICACIONES TÉCNICAS

Body Size	3/4"
Burst Pressure	14800 PSI (1000 bar)
Factory Part Number	K6F6
Hex	1-5/16"
Length	2.43" (61.7mm)
Material	Steel
Maximum OD	1.44" (36.6mm)
Maximum Operating Pressure	4000 PSI (275 bar)
Temperature Range	-40°F to +250°F (-40°C to +121°C)
Thread	Female NPTF
Thread Size	3/4"-14
Weight Lb	0.4100

KMX

2645 Executive Park Drive, Weston, Fort Lauderdale, FL 33331, EEUU
sales@kmxusa.us

www.kmxusa.us