GROOVED LIGHTWEIGHT FLEXIBLE COUPLING- SERIES L, STYLE 10



** Imágenes referenciales*
*** Algunas características pueden variar sin previo aviso, venta sujeta a stock disponible*

FECHA
: 11/23/2026 08:57 PM

SKU
: 24864

MARCA
: DIXON VALVE

MODELO
: L03BU

Applications:
Applications include: general purpose, mining, irrigation, and compressed air where a deflection of 5% or less is required.

Use:
Designed for applications requiring moderate internal pressure or where weight is a factor.

Specifications:
Underwriters Listed
Factory Mutual approved
Bolts: 2
Bolt Size: 1/2"
Bolt Length: 2-3/4"

Features:
Comparable to Victaulic's #75 and Grinnell's #7000

Construction:
Rust inhibiting paint

Safety notes:
WARNING: Cancer and Reproductive Harm- www.P65Warnings.ca.gov

2645 Executive Park Drive, Weston, Fort Lauderdale, FL 33331, EEUU
sales@kmxusa.us
www.kmxusa.us

ESPECIFICACIONES TÉCNICAS

Factory Part Number	L03BU
Material	Ductile Iron
Maximum Operating Pressure	300 PSI at 70°F (21°C)
Nominal Size	3"
Pipe OD	3.50"
Seal	Buna-N
Weight Lb	2.7400

KMX
2645 Executive Park Drive, Weston, Fort Lauderdale, FL 33331, EEUU
sales@kmxusa.us
www.kmxusa.us