WILKERSON FRL'S L16 ECONOMIST® COMPACT LUBRICATOR



** Imágenes referenciales*
*** Algunas características pueden variar sin previo aviso, venta sujeta a stock disponible*

FECHA
: 11/24/2026 12:27 AM

SKU
: 26388

MARCA
: DIXON VALVE

MODELO
: L16-03A

Applications:
Designed so that all of the oil flow observed in the sight dome is broken into a mist and delivered via the airflow to the application.

Use:
The oil in the bowl can be filled or replenished without interrupting airflow or bleeding pressure from the system.
Once the oil-fill cap is removed, the bowl is depressurized and isolated from line pressure, and the bowl itself can then be removed for faster refill, if desired.
The bowl can be filled right to the top.
For all Wilkerson lubricators, use any petroleum-base, non-detergent light weight oil (SAE 10/150 SSU) which will readily break up into a mist, i.e., Mobil DTE light or comparable oil. Do not use any synthetic oil or oils containing additives or solvents.

Features:
5 oz. bowl
Full view sight dome
Transparent Bowl

Safety notes:
FRL\'s are designed for air service only, unless otherwise indicated.
SCFM ratings at 150 PSIG inlet pressure
WARNING: Cancer and Reproductive Harm- www.P65Warnings.ca.gov

2645 Executive Park Drive, Weston, Fort Lauderdale, FL 33331, EEUU
sales@kmxusa.us
www.kmxusa.us

ESPECIFICACIONES TÉCNICAS

Description	Transparent Bowl
Factory Part Number	L16-03A
Flow	58.5 SCFM
Maximum Operating Pressure	150 PSIG (10.3 Bar)
Port	3/8"
Temperature Range	32°F to 125°F (0°C to 52°C)
Weight Lb	1.7800

KMX
2645 Executive Park Drive, Weston, Fort Lauderdale, FL 33331, EEUU
sales@kmxusa.us
www.kmxusa.us