L17 SERIES 1 FRL'S JUMBO MICRO-FOG LUBRICATOR



** Imágenes referenciales*
*** Algunas características pueden variar sin previo aviso, venta sujeta a stock disponible*

FECHA
: 11/24/2026 12:50 AM

SKU
: 26394

MARCA
: DIXON VALVE

MODELO
: L17-800A

Applications:
Micro-fog lubricators, identified by a red adjusting screw, are used for applications containing one or more points of lubrication, cylinders and multiple or single tools.

Features:
Metal Bowl with Sight Glass
1 qt. reservoir
Oil level sight gauge
One turn threaded bowl attachment permits easy maintenance

How it works:
Air flow through the lubricator lifts oil from the reservoir to the sight-feed dome. Oil is dropped into the fog generator and atomized into a fine mist. Lightweight particles are delivered downstream for lubrication. Heavier particles fall back into the reservoir.
The micro-fog lubricator delivers 10% of the oil drops visible through the transparent sight-feed dome.

Safety notes:
FRL\'s are designed for air service only, unless otherwise indicated.
Micro-fog lubricators cannot be filled under pressure.
SCFM ratings at 90 PSIG inlet pressure
WARNING: Cancer and Reproductive Harm- www.P65Warnings.ca.gov

2645 Executive Park Drive, Weston, Fort Lauderdale, FL 33331, EEUU
sales@kmxusa.us
www.kmxusa.us

ESPECIFICACIONES TÉCNICAS

Factory Part Number	L17-800A
Flow	275 SCFM
Inlet Pressure	250 PSI
Maximum Temperature	175°F (79°C)
Port	1"
Weight Lb	4.0800

KMX
2645 Executive Park Drive, Weston, Fort Lauderdale, FL 33331, EEUU
sales@kmxusa.us
www.kmxusa.us