WILKERSON FRL'S L28 ECONOMIST® STANDARD LUBRICATOR



** Imágenes referenciales*
*** Algunas características pueden variar sin previo aviso, venta sujeta a stock disponible*

FECHA
: 11/24/2026 01:03 AM

SKU
: 26414

MARCA
: DIXON VALVE

MODELO
: L28-06AMB

Use:
To adjust and set oil delivery rate the unit must be pressurized and air must be flowing through the unit. Turn the sight dome, located on the top of the unit, counter clockwise to initiate oil delivery. If flow increases or decreases, the oil delivery rate will increase or decrease proportionally. Turning the sight dome clockwise will stop oil delivery.
Can be filled under pressure
For all Wilkerson lubricators, use any petroleum-base, non-detergent light weight oil (SAE 10/150 SSU) which will readily break up into a mist, i.e., Mobil DTE light or comparable oil. Do not use any synthetic oil or oils containing additives or solvents.

Features:
6.11 oz. bowl
Metal Bowl
Manual drain
High flow capacity

Safety notes:
FRL\'s are designed for air service only, unless otherwise indicated.
SCFM ratings at 150 PSIG inlet pressure
WARNING: Cancer and Reproductive Harm- www.P65Warnings.ca.gov

2645 Executive Park Drive, Weston, Fort Lauderdale, FL 33331, EEUU
sales@kmxusa.us
www.kmxusa.us

ESPECIFICACIONES TÉCNICAS

Description	Metal Bowl
Factory Part Number	L28-06AMB
Flow	150 SCFM
Maximum Operating Pressure	250 PSIG (17.2 Bar)
Port	3/4"
Temperature Range	32°F to 150°F (0°C to 65.5°C)
Weight Lb	1.6500

KMX
2645 Executive Park Drive, Weston, Fort Lauderdale, FL 33331, EEUU
sales@kmxusa.us
www.kmxusa.us